

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number
WO 2004/046512 A1

- (51) International Patent Classification⁷: **F01L 13/00**, 1/34 (74) Agent: MESSULAM, Alec, Moses; A. Messulam & Co. Ltd., 43-45 High Road, Bushey, Hertfordshire WD23 1EE (GB).
- (21) International Application Number: PCT/GB2003/004864 (81) Designated States (*national*): JP, US.
- (22) International Filing Date: 12 November 2003 (12.11.2003) (84) Designated States (*regional*): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- (25) Filing Language: English
- (26) Publication Language: English Declaration under Rule 4.17:
— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations JP, European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR)
- (30) Priority Data: 0226842.3 16 November 2002 (16.11.2002) GB
- (71) Applicant (*for all designated States except US*): MECHA-DYNE PLC [GB/GB]; Park Farm Estate, Kirtlington, Oxfordshire OX5 3JQ (GB). Published:
— with international search report
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): METHLEY, Ian [GB/GB]; 52 Churchill Way, Long Hanborough, Witney, Oxfordshire OX29 8JL (GB). For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ENGINE WITH VARIABLE LIFT VALVE MECHANISM



(57) Abstract: An internal combustion engine is described having a valve mechanism which comprises a gas exchange poppet valve (14), a camshaft (10) rotatable in synchronism with the engine crankshaft and having a cam (12) for operating the valve (14), a valve actuator (20) acting on the poppet valve (14) to open and close the valve, and an intermediate rocker (30) having a follower (34) acted upon by the cam (12) and a contoured surface (36) that acts on the valve actuator (20) to open and close the valve (14) in synchronism with the rotation of the cam (12), the intermediate rocker (30) having a pivot axis that is movable in order to vary the valve lift. In the invention, the intermediate rocker (30) is mounted about a pivot shaft (32) that is moved to vary the valve lift in response to rotation of the pivot shaft (32) about its own axis, and the pivot shaft (32) is constrained to move along a path which is such that, while the cam follower (34) is on the base circle of the cam (12), the valve actuator (20) remains stationary and a substantially constant clearance is maintained between the contoured surface (36) of the intermediate rocker (30) and the valve actuator (20) during displacement of the pivot shaft along the path.

- 1 -

ENGINE WITH VARIABLE LIFT VALVE MECHANISMField of the invention

5 The present invention relates to An internal combustion engine having a valve mechanism which comprises a gas exchange poppet valve, a camshaft rotatable in synchronism with the engine crankshaft and having a cam for operating the valve, a valve actuator acting on the poppet valve to
10 open and close the valve, and an intermediate rocker having a follower acted upon by the cam and a contoured surface that acts on the valve actuator to open and close the valve in synchronism with the rotation of the cam, the intermediate rocker having a pivot axis that is movable in
15 order to vary the valve lift.

Background of the invention

20 The known BMW Valvetronic valve mechanism, as described for example in EP 1039103, operates in the manner described above and is believed to constitute the closest published prior art to the present invention. In the known mechanism, the intermediate rocker pivots about a point at its upper end which can be moved from side to side by means of a cam.
25 At a point between its two ends, the intermediate rocker carries the cam follower, its lower end being contoured and in contact with the valve actuating rocker.

30 The valve mechanism described in EP 1039103 suffers from several disadvantages. First, the mechanism requires a special cylinder head that increases the overall height of the engine and can cause packaging problems. Second, the intermediate member is not positively retained in the cylinder head and is merely allowed to free float, being
35 urged against its various contact points (at the cam and at its pivot) by means of a spring. Third, a complex control

- 2 -

mechanism is required to enable the valve events of several valves to be controlled at the same time.

Summary of the invention

5

In accordance with the present invention, an internal combustion engine as set forth above is characterised in that the intermediate rocker is mounted about a pivot shaft that is moved to vary the valve lift in response to rotation
10 of the pivot shaft about its own axis, and the pivot shaft is constrained to move along a path which is such that, while the cam follower is on the base circle of the cam, the valve actuator remains stationary and a substantially constant clearance is maintained between the contoured
15 surface of the intermediate rocker and the valve actuator during displacement of the pivot shaft along the path.

In the present invention, the intermediate rocker is mounted on a pivot shaft and is therefore positively
20 retained in the engine. Furthermore, because movement of the pivot shaft is effected by simply rotating it about its own axis, the requirement for a complex control mechanism is obviated. Because the intermediate rocker no longer free floats, the invention also ensures that the clearance
25 between the intermediate rocker and the valve actuator is not affected by position of the pivot shaft.

In the preferred embodiment of the invention, the pivot shaft is located on the intermediate rocker between the cam
30 follower and the contoured surface that actuates the valve. Consequently, the pivot shaft is located lower in the engine, avoiding the need to increase the overall height of the cylinder head. This also has the effect of reducing the rotational inertia of the intermediate rocker.

35

It is also important to note that whereas in the prior art the intermediate rocker pivots about a single point at

- 3 -

its upper end, in the present invention the intermediate rocker is pivoted about a shaft and it therefore less prone to wear.

5 The valve actuator is preferably itself a rocker (hereinafter termed the valve actuating rocker to distinguish it from the intermediate rocker) pivoted at one end, acting on the valve at its other and having between its ends a part-cylindrical contact surface of a roller follower
10 acted upon by the contoured surface of the intermediate rocker.

 In order to maintain a constant clearance between the valve actuating rocker and the contoured surface of the
15 intermediate rocker, it is preferred to provide a link to constrain the pivot shaft of the intermediate rocker to move in an arc centred on the axis of the roller or cylindrical contact surface of the valve actuating rocker.

20 In order to move the pivot shaft of the intermediate rocker, it is preferred for the shaft to pass through a bore in an eccentric sleeve rotatably supported in a stationary bearing block of the engine. The rotation of the eccentric sleeve will in this case result in translation of the axis
25 of the shaft.

 The eccentric sleeve is advantageously coupled to the shaft by means of a pin which is free to slide relative to at least one of the sleeve and the shaft. In practice, the
30 shaft will normally be connected to at least two sleeves supported in bearing blocks and by rotating the shaft, all the sleeves will be moved by equal amounts.

 The movement of the pivot shaft of the intermediate
35 rocker will not only result in the valve lift being varied but in a change in the timing of the valve event. It is possible to provide a phase change mechanism between the

- 4 -

engine crankshaft and the camshaft to compensate for, or increase, this modification of the engine timing as desired.

Conveniently, the fixed point on which the valve
5 actuating rocker rests in the engine comprises a hydraulic lash adjuster.

Brief description of the drawings

10 The invention will now be described further, by way of example, with reference to the accompanying drawings, in which :

Figure 1 is a perspective view of the valve mechanism of an engine of the present invention,

15 Figure 2 shows an end view of the valve mechanism of Figure 1 with the valve closed and the pivot shaft of the intermediate rocker in a position to achieve maximum valve lift,

Figure 3 shows an end view similar to that of
20 Figure 2, with the valve fully opened and the pivot shaft of the intermediate rocker in a position to achieve maximum valve lift,

Figure 4 shows an end view similar to that of
Figure 2, with the valve closed and the pivot shaft of
25 the intermediate rocker in a position to achieve minimum valve lift,

Figure 5 shows an end view similar to that of
Figure 2, with the valve fully opened and the pivot
shaft of the intermediate rocker in a position to
30 achieve minimum valve lift,

Figure 6 shows a side view of the valve mechanism complete with a phase change mechanism for varying the phase of the camshaft relative to the engine crankshaft, and

35 Figure 7 is a section along the line A-A in Figure 6.

- 5 -

Detailed description of the preferred embodiment

The valve mechanism in the drawings is fitted to a cylinder head of an engine which, in the interest of clarity has not been shown in full. A camshaft 10 driven by the engine crankshaft through a phase change mechanism 50 (see Fig. 6) is suitably journaled in the cylinder head. the camshaft 10 carries cams 12 which act by way of the mechanism to be described below on two gas exchange poppet valves 14, which may be intake or exhaust valves. Each poppet valve 14 is slidable in a valve guide 16 that is driven into the cylinder head. When the valve is closed by a spring which is not shown, the enlarged head of the valve 14 seals, against a valve seat 18 that also forms part of the engine cylinder head.

Each valve 14 is opened and closed by a valve actuating rocker 20, herein termed the valve actuating rocker, which is pivoted at one end on a hydraulic lash adjuster 22 (shown in Figures 2 to 5). The opposite end of the valve actuating rocker 20 acts on the upper end of the stem of the valve 14 and a follower roller 24 is fitted to the valve actuating rocker 20 near its mid-point.

An intermediate rocker 30 is pivotably mounted on a shaft 32. One end of the intermediate rocker 30 carries a cam follower roller 34 and on its opposite end there is formed a contoured surface 36 which acts on the follower roller 24 of the valve actuating rocker 20. As the cam 12 rotates, the intermediate rocker pivots about the shaft 32 and its contoured surface 36 acts on the roller 24 to pivot the valve actuating rocker 20 about the hydraulic lash adjuster 22 and thereby open and close the valve 14.

Because of the shape of the contoured surface 36, movement of the pivot shaft 32 from left to right as viewed

- 6 -

in Figures 2 to 5 has the effect of reducing the valve lift. This can best be seen from a comparison of Figures 2 to 5.

5 In Figure 2, the roller 24 is in contact with the contoured surface mid-way along its length when the cam follower roller 34 is in contact with the base circle of the cam 12. When the roller 34 moves on to the lobe of the cam 12, as shown in Figure 3, the right hand end (as viewed) of the contoured surface 36 fully depresses the valve actuating
10 rocker 20 to open the valve with maximum lift.

By contrast, in Figure 4, the pivot shaft 32 has been moved to the right so that when the roller 34 is on the base circle of the cam 12 the follower 24 is in contact with the
15 contoured surface 36 near its left hand end. When, as shown in Figure 5, the roller 34 moves on to the lobe of the cam 12, the follower 24 does not reach the right hand end of the contoured surface 36 and the valve is not opened to the same extent. Thus by moving the pivot shaft 32 from left to
20 right, as viewed, the valve lift can be set to any desired value between its two limits.

It is important to ensure that the act of moving the shaft 32 to vary the valve lift does not affect the
25 clearance between the roller 24 and the contoured surface 36. For this clearance to remain constant, the locus of the shaft 32 is required to be an arc centred on the axis of the follower roller 24.

30 In the illustrated embodiment of the invention, the shaft is constrained to move along such a path by means of a pair of links 38. The shaft 32 is rotatably mounted in the latter links 38 and the lower end of each link 38 is pivotably mounted on a respective pivot pin that is
35 stationarily mounted in the engine with its axis in line with the axis of the follower rollers 24 of the valve actuating rockers 20. Each pin projects from a small block

- 7 -

40 that is bolted to a post 42 which forms part of the engine cylinder head.

5 The shaft 32 passes through two cylindrical bores formed in bearing blocks (not shown) which are secured to the engine cylinder head. Sleeves 44 with eccentric bores are interposed between the shaft 32 and the bearing blocks, the shaft 32 being received with clearance in the bores of the sleeves 44. Each sleeve 44 is coupled for rotation with
10 the shaft 32 by means of a pin 46 (see Fig. 7) which is a sliding fit in at least one of the shaft 32 and the sleeve 44.

If the shaft 32 is rotated, the eccentric sleeves 44
15 will rotate in the bearing blocks and thereby displace the axis of the shaft. The clearance between the shaft 32 and the sleeves 44 and the sliding movement of the coupling pins are required because the path followed by the shaft 32 is dictated by the links 38 and not by the sleeves 44. The
20 eccentric sleeves 44 serve merely as a convenient manner to urge the shaft 32 to the left or to the right uniformly along its length.

A phase changing mechanism 50 of any suitable design
25 (of which there are numerous examples in the prior art) is used to vary the phase of the camshaft 10 in relation to the engine crankshaft. The phase change mechanism 50 may, for example, be used to compensate for the variation in event timing that accompanies the variation in valve lift achieved
30 by the mechanism described.

It will be appreciated by the person skilled in the art that various modifications may be made to the described valve mechanism without departing from the scope of the
35 invention as set out in the appended claims. For example, in the described embodiment, separate cams and intermediate rockers are employed to open the two valves of a cylinder,

- 8 -

but it would be alternatively possible to employ a single intermediate rocker having a single cam follower and two profiled surfaces to act on the two valves. Such a construction permits both valves to be actuated concurrently
5 by a single cam lobe.

As above described, the cam lobes 12 and the contoured surfaces 36 associated with the respective valves were assumed to be identical so that the two valves of a cylinder
10 would always open at the same time and by the same amount as one another. It is alternatively possible however for the cam profiles and/or the contoured surfaces of the intermediate rockers actuating the two valves to have a
different geometry from one another, such that the valve
15 lift characteristics of the two valves differ from one another as the valve lift is reduced.

- 9 -

CLAIMS

1. An internal combustion engine having a valve mechanism which comprises

5 a gas exchange poppet valve (14),
a camshaft (10) rotatable in synchronism with the engine crankshaft and having a cam (12) for operating the valve (14),

10 a valve actuator (20) acting on the poppet valve (14) to open and close the valve, and

an intermediate rocker (30) having a follower (34) acted upon by the cam (12) and a contoured surface (36) that acts on the valve actuator (20) to open and close the valve (14) in synchronism with the rotation of the cam (12), the
15 intermediate rocker (30) having a pivot axis that is movable in order to vary the valve lift,

characterised in that

the intermediate rocker (30) is mounted about a pivot shaft (32) that is moved to vary the valve lift in response
20 to rotation of the pivot shaft (32) about its own axis, and

the pivot shaft (32) is constrained to move along a path which is such that, while the cam follower (34) is on the base circle of the cam (12), the valve actuator (20) remains stationary and a substantially constant clearance is
25 maintained between the contoured surface (36) of the intermediate rocker (30) and the valve actuator (20) during displacement of the pivot shaft along the path.

2. An engine as claimed in claim 1, wherein the pivot
30 shaft (32) is located on the intermediate rocker (30) between the cam follower (34) and the contoured surface (36).

3. An engine as claimed in claim 1 or 2, wherein the
35 valve actuator is constructed as a valve actuating rocker (20) pivoted at one end, acting on the valve (14) at its other end and having between its ends a part-cylindrical contact

- 10 -

surface or a roller follower (24) acted upon by the contoured surface (36) of the intermediate rocker (30).

4. An engine as claimed in claim 3, wherein the pivot
5 at the said one end of the valve actuating rocker (20) comprises a hydraulic lash adjuster (22).

5. An engine as claimed in claim 3 or 4, wherein the
pivot shaft (32) is journalled in a link (38) that
10 constrains the pivot shaft (32) of the intermediate rocker (30) to move along arc centred on the axis of the roller (24) or cylindrical contact surface of the valve actuating rocker (20).

15 6. An engine as claimed in claim 5, wherein the pivot shaft (32) passes with clearance through a bore in an eccentric sleeve (44) rotatably supported in a stationary bearing block of the engine.

20 7. An engine as claimed in claim 6, wherein the eccentric sleeve (44) is coupled to the shaft by means of a pin (46) which is free to slide relative to at least one of the sleeve (44) and the shaft (32).

25 8. An engine as claimed in any preceding claim, wherein a phase change mechanism (50) is provided between the engine crankshaft and the camshaft (10).

9. An engine as claimed in any preceding claim,
30 having two valve mechanisms controlling the flow of gas into or out of each engine cylinder, wherein the cam profiles and/or the contoured surfaces of the intermediate rockers actuating the two valves of each cylinder have a different geometry from one another, such that the valve lift
35 characteristics of the two valves differ from one another as the valve lift is reduced.

1/3




Fig. 1

2/3




Fig. 2




Fig. 3




Fig. 4




Fig. 5

3/3




Fig. 6




Fig. 7

INTERNATIONAL SEARCH REPORT

International application No
PCT/GB 03/04864

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 F01L13/00 F01L1/34

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 F01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 397 270 A (AOYAMA SHUNICHI) 9 August 1983 (1983-08-09) column 2, line 7-19 column 3, line 47-65 figures	1,2
A	DE 197 08 484 A (BAYERISCHE MOTOREN WERKE AG) 10 September 1998 (1998-09-10) the whole document	1,3,4

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *G* document member of the same patent family

Date of the actual completion of the international search

20 February 2004

Date of mailing of the international search report

27/02/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Klinger, T

INTERNATIONAL SEARCH REPORT

International application No
PCT/GB 03/04864

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4397270	A	09-08-1983	JP 1379545 C	28-05-1987
			JP 55137305 A	27-10-1980
			JP 61048614 B	24-10-1986
			AU 529142 B2	26-05-1983
			AU 5742080 A	16-10-1980
			CA 1148807 A1	28-06-1983
			DE 3014005 A1	16-10-1980
			FR 2453979 A1	07-11-1980
			GB 2047801 A ,B	03-12-1980
DE 19708484	A	10-09-1998	DE 19708484 A1	10-09-1998